

FOR SALE

2x Ex-demo SlomoTV Simple R 442 1080p Server

Slomo RU4H-SR-2T Simple R 442 Exchange
Compact replay and recording server

Including 1x Controller per device

4x Record channels (Input)

4x Search channels

2x Playback channels (Output)

Included Options: All options permanently included

2x, 3x & 4x SloMo in 1080p

Technical details down below

Built in 2016



Short description:

The slomo.tv RU4H SR 2T Simple R 442 Exchange is a compact professional instant replay and recording server from the Simple R series, designed for mobile productions, OB vans, smaller studios, sports events, and backup/exchange applications.

Housed in a lightweight 1RU 19" chassis, the system delivers a full-featured replay workflow in a highly portable form factor.

Simple R 442 Architecture

Replay Configuration

- 4 × recording channels
- 4 × synchronized search channels
- 2 × playback channels with transitions and FX

The 442 configuration enables:

- simultaneous multi-camera recording
- frame-accurate analysis and replay
- parallel playout for broadcast or live production

Video I/O

Inputs

- 8 × bidirectional SDI ports
- Supports:
 - HD-SDI
 - SD-SDI
 - optional 3G-SDI (model/options dependent)

Outputs

- 2 × SDI outputs
 - Output 1: program/playout with transitions
 - Output 2 configurable as:
 - preview
 - multiviewer
 - alpha channel
 - delay output/video server

Supported Video Formats

- HD and SD formats (50 Hz & 59.94 Hz)
 - 1920×1080i / PsF
 - 1280×720p
 - PAL / NTSC
- Optional 3G-SDI support:
 - 1920×1080p50 / p59.94
 - 1920×1080p100 / p119.88
- 16:9 and 4:3 aspect ratios supported

Multiviewer & User Interface

- Integrated multiviewer
 - up to 9 video windows in the main UI
 - up to 16 windows via dedicated graphics or SDI output
- Display outputs:
 - 2 × HDMI
 - 1 × DisplayPort
- Simultaneous monitoring of:
 - recording channels
 - search positions
 - clips and markers

Audio

- Embedded audio support:
 - up to 32 audio channels via HD/SD-SDI
 - 24-bit / 48 kHz
- Replay output:
 - 8 embedded audio channels in SDI output

Storage & Recording

- 2 TB internal SSD storage (“2T”)
- Optimized for:
 - high sustained write speeds
 - vibration-resistant mobile operation

Supported codecs

- DVCPro 50
- DVCPro HD

Optional codec support

- ProRes 422
- DNxHD
- XDCAM 422 / 35
- AVC-Intra
- XAVC

Control & Operation

Compatible with professional slomo.tv control panels including:

- Control ZR
- Jog/Shuttle controllers
- T-Bar operation

Alternative operation via keyboard and mouse.

Key features:

- automatic clip creation
- playlist generation
- highlight editing and compilation

Networking & Integration

- 1 × Gigabit Ethernet
- Media exchange between:
 - Simple R servers
 - other slomo.tv systems

Export formats

- QuickTime
- MXF
- MP4

Mechanical & Power

- 19" rackmount chassis
- 1RU height
- lightweight and travel-friendly design
- 110V / 220V, 50/60 Hz power support
- optional redundant power supply

Typical Applications

- mobile sports productions
- OB vans
- club and league productions
- backup/exchange replay servers
- coaching and analysis replay systems

Pictures of the Equipment:





Price on request:

Excl. VAT

Excl. shipping & insurance costs

Excl. custom fees

For further information please contact:

Otmar Valzachi

sports tv media distribution GmbH

Paradeisergasse 9

9020 Klagenfurt

AUSTRIA

Tel:+43 463 908000

Fax:+43 463 908000 99

Mobile:+43 676 848606211

email: ov@stvmd.com

<http://www.stvmd.com>